io surface



		PRODUCT
	Name	IO SURFACE UL 30º 2700K NT
	Reference	U2630120NT
	Color	Textured black
	Category	SURFACE
antitude of the second s		
		LIGHT SOURCE
	Туре	LED
	Gross luminous flux	Depending on Mounting Accessories Lm
	Color temperature	2700 K
	Chromatic stability	MacAdam Step 2
	Color Rendering Index	CRI>90
	Power	 Depending on Mounting Accessories W
	Current	Depending on Mounting Accessories mA
DIMENSIONS	LED lifespan	L90B10>55.000h
	Lighting efficiency	 0 m
	Delivered luminous flux Light beam angle	0 Lm 30°
	Delivered luminous flux	
Ø1.42in Ø1.57in (36mm) (40mm)	Delivered luminous flux	
Ø1.42in Ø1.57in	Delivered luminous flux	30°
Ø1.42in Ø1.57in (36mm) (40mm)	Delivered luminous flux Light beam angle	30°
Ø1.42in Ø1.57in (36mm) (40mm)	Delivered luminous flux Light beam angle Driver	30° LIGHTING FIXTURE ELECTRICAL DATA Requires remote driver
01.42in 01.57in (36mm) (40mm) 3.30in (84mm)	Delivered luminous flux Light beam angle Driver Power values of the system	30° LIGHTING FIXTURE ELECTRICAL DATA Requires remote driver W
Ø1.42in Ø1.57in (36mm) (40mm)	Delivered luminous flux Light beam angle Driver Power values of the system Frequency	30° LIGHTING FIXTURE ELECTRICAL DATA Requires remote driver W Depending on Mounting Accessories
Ø1.42in Ø1.57in (<u>36mm</u>) (40mm) 3.30in (84mm)	Delivered luminous flux Light beam angle Driver Power values of the system Frequency	30° LIGHTING FIXTURE ELECTRICAL DATA Requires remote driver W Depending on Mounting Accessories
Ø1.42in Ø1.57in (36mm) (40mm) 3.30in (84mm)	Delivered luminous flux Light beam angle Driver Power values of the system Frequency	30° LIGHTING FIXTURE ELECTRICAL DATA Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories
Ø1.42in Ø1.57in (36mm) (40mm) 3.30in (84mm) ACCESORIES	Delivered luminous flux Light beam angle Driver Power values of the system Frequency Dimming	30° LIGHTING FIXTURE ELECTRICAL DATA Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA
01.42in 01.57in (36mm) (40mm) 3.30in (84mm) ACCESORIES	Delivered luminous flux Light beam angle Driver Power values of the system Frequency Dimming Environmental location	30° LIGHTING FIXTURE ELECTRICAL DATA Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP
01.42in 01.57in (40mm) 3.30in (84mm) ACCESORIES	Delivered luminous flux Light beam angle Driver Power values of the system Frequency Dimming Environmental location Junction box cover	30° LIGHTING FIXTURE ELECTRICAL DATA Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box
Ø1.42in Ø1.57in (36mm) (40mm) 3.30in (84mm) ACCESORIES	Delivered luminous flux Light beam angle Driver Power values of the system Frequency Dimming Environmental location Junction box cover Junction box cover color	30° LIGHTING FIXTURE ELECTRICAL DATA Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consult
01.42in (36mm) (40mm) 3.30in (84mm) ACCESORIES MIXER DIFFUSER ANTI-GLARE HONEYCOMB	Delivered luminous flux Light beam angle Driver Power values of the system Frequency Dimming Environmental location Junction box cover Junction box cover color Junction box cover measurements	30° LIGHTING FIXTURE ELECTRICAL DATA Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consult Ø5.51 in Ø140 mm
Ø1.42in Ø1.57in (36mm) (40mm) 3.30in (84mm) ACCESORIES	Delivered luminous flux Light beam angle Driver Power values of the system Frequency Dimming Environmental location Junction box cover Junction box cover color Junction box cover color Swivel angle	30° LIGHTING FIXTURE ELECTRICAL DATA Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consult Ø5.51 in Ø140 mm 325°
Ø1.42in (36mm) (40mm) 3.30in (84mm) ACCESORIES MIXER DIFFUSER ANTI-GLARE HONEYCOMB	Delivered luminous flux Light beam angle Driver Power values of the system Frequency Dimming Environmental location Junction box cover Junction box cover color Junction box cover measurements Swivel angle Rotation angle	30° LIGHTING FIXTURE ELECTRICAL DATA Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consult Ø5.51 in Ø140 mm 325° 355°
01.42in 01.57in (36mm) (40mm) 3.30in (84mm) ACCESORIES MIXER DIFFUSER ANTI-GLARE HONEYCOMB	Delivered luminous flux Light beam angle Driver Power values of the system Frequency Dimming Environmental location Junction box cover Junction box cover color Junction box cover measurements Swivel angle Rotation angle	30° LIGHTING FIXTURE ELECTRICAL DATA Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consult Ø5.51 in Ø140 mm 325° 355° 0.76 lb 343 gr
01.42in (36mm) (40mm) 3.30in (84mm) ACCESORIES MIXER DIFFUSER ANTI-GLARE HONEYCOMB	Delivered luminous flux Light beam angle Driver Power values of the system Frequency Dimming Environmental location Junction box cover Junction box cover color Junction box cover measurements Swivel angle Rotation angle Weight	30° LIGHTING FIXTURE ELECTRICAL DATA Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consult Ø5.51 in Ø140 mm 325° 355° 0.76 ib 343 gr 0.93 ib 423 gr

IO is a LED spotlight miniaturised in a fixture that is so small that it fits on the palm of your hand. Designed for accent lighting applications, its small dimensions mean it can be fitted in display cabinets, shop windows and small places without generating an invasive presence on the scene.

JOKERLIGHT LLC 2750 NW 84th Ave · Doral · FL 33122 (USA) Info@jokerlight.com · www.jokerlight.com

PREMIO ADCV 2017 ORO 05-04-25 / 00:55

5Year





PRODUCT

Model
Reference
Category


PRODUCT
Beam Mixer Diffuser
0805-01-00
Accessories
NOT SOLD SEPARATELY AFFECTS THE LIGHTING PARAMETERS

The Beam Mixer Diffuser is used to smooth beam artifacts caused by parabolic, Fresnel, or TIR lens collimators without significant broadening.

The unique mixing design provides superior far-field smoothing and color mixing with high on-axis brightness. Compared with traditional diffusers, it maintains higher central beam candlepower (CBCP), and produce less undesirable "field light" at higher angles.







PRODUCT

Model
Reference
Colour
Category

PRODUCT	
Anti-glare Honeycomb Louver	
0806-00-00 WT NT	
WT □ Textured white NT ■ Textured black	
Accessories	
NOT SOLD SEPARATELY	A
AFFECTS THE LIGHTING PARAMETERS	\odot

Accessory made up of louver in the shape of a honeycomb panel to reduce glare and the effects of direct rays of vision.

