io surface



		PRODUCT
	Name	IO SURFACE UL 30° 4000K NT
	Reference	U2630122NT
	Color	Textured black
	Category	SURFACE
		LIGHT SOURCE
	Туре	LED
	Gross luminous flux	Depending on Mounting Accessories Lm
	Color temperature	4000 K
	Chromatic stability	MacAdam Step 2
	Color Rendering Index	CRI>90
	Power	Depending on Mounting Accessories W
	Current	Depending on Mounting Accessories mA
DIMENSIONS	LED lifespan	L90B10>55.000h
	Lighting efficiency	89%
	Delivered luminous flux	0 Lm
Ø1.42in Ø1.57in		
Ø1.42in Ø1.57in (36mm) (40mm)	Delivered luminous flux	0 Lm
Ø1.42in Ø1.57in	Delivered luminous flux	0 Lm 30°
Ø1.42in Ø1.57in (36mm) (40mm)	Delivered luminous flux Light beam angle	0 Lm 30° LIGHTING FIXTURE ELECTRICAL DATA
Ø1.42in Ø1.57in (36mm) (40mm)	Delivered luminous flux Light beam angle Driver	0 Lm 30° LIGHTING FIXTURE ELECTRICAL DATA Requires remote driver
Ø1.42in Ø1.57in (36mm) (40mm)	Delivered luminous flux Light beam angle Driver Power values of the system	0 Lm 30° LIGHTING FIXTURE ELECTRICAL DATA Requires remote driver W
Ø1.42in Ø1.57in (<u>36mm</u>) (40mm) 3.30in (84mm)	Delivered luminous flux Light beam angle Driver Power values of the system Frequency	0 Lm 30° LIGHTING FIXTURE ELECTRICAL DATA Requires remote driver W Depending on Mounting Accessories
Ø1.42in Ø1.57in (36mm) (40mm) 3.30in (84mm)	Delivered luminous flux Light beam angle Driver Power values of the system Frequency	0 Lm 30° LIGHTING FIXTURE ELECTRICAL DATA Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories
Ø1.42in Ø1.57in (40mm) 3.30in (84mm) ACCESORIES	Delivered luminous flux Light beam angle Driver Power values of the system Frequency Dimming	0 Lm 30° LIGHTING FIXTURE ELECTRICAL DATA Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA
01.42in 01.57in (36mm) (40mm) 3.30in (84mm) ACCESORIES	Delivered luminous flux Light beam angle Driver Power values of the system Frequency Dimming Environmental location	0 Lm 30° LIGHTING FIXTURE ELECTRICAL DATA Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP
01.42in 01.57in (40mm) 3.30in (84mm) ACCESORIES	Delivered luminous flux Light beam angle Driver Power values of the system Frequency Dimming Environmental location Junction box cover	0 Lm 30° LIGHTING FIXTURE ELECTRICAL DATA Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box
01.42in 01.57in (3dmm) (40mm) 3.30in (84mm) ACCESORIES	Delivered luminous flux Light beam angle Driver Power values of the system Frequency Dimming Environmental location Junction box cover Junction box cover color	0 Lm 30° LIGHTING FIXTURE ELECTRICAL DATA Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consult
Ø1.42in Ø1.57in (36mm) (40mm) 3.30in (84mm) ACCESORIES	Delivered luminous flux Light beam angle Driver Power values of the system Frequency Dimming Environmental location Junction box cover Junction box cover color Junction box cover measurements	0 Lm 30° LIGHTING FIXTURE ELECTRICAL DATA Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consult Ø5.51 in Ø140 mm
Ø1.42in Ø1.57in (36mm) (40mm) 3.30in (84mm) ACCESORIES	Delivered luminous flux Light beam angle Driver Power values of the system Frequency Dimming Environmental location Junction box cover Junction box cover color Junction box cover color Swivel angle	0 Lm 30° LIGHTING FIXTURE ELECTRICAL DATA Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consult Ø5.51 in Ø140 mm 325°
01.42in 01.57in (40mm) 3.30in (84mm) ACCESORIES	Delivered luminous flux Light beam angle Driver Power values of the system Frequency Dimming Environmental location Junction box cover Junction box cover color Junction box cover measurements Swivel angle Rotation angle	0 Lm 30° LIGHTING FIXTURE ELECTRICAL DATA Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consult Ø5.51 in Ø140 mm 325° 355°
01.42in (36mm) (40mm) 3.30in (84mm) ACCESORIES MIXER DIFFUSER ANTI-GLARE HONEYCOMB	Delivered luminous flux Light beam angle Driver Power values of the system Frequency Dimming Environmental location Junction box cover Junction box cover color Junction box cover measurements Swivel angle Rotation angle	0 Lm 30° LIGHTING FIXTURE ELECTRICAL DATA Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consult Ø5.51 in Ø140 mm 325° 355° 0.76 ib 343 gr
01.42in (36mm) (40mm) 3.30in (84mm) ACCESORIES MIXER DIFFUSER ANTI-GLARE HONEYCOMB	Delivered luminous flux Light beam angle Driver Power values of the system Frequency Dimming Environmental location Junction box cover Junction box cover color Junction box cover measurements Swivel angle Rotation angle Weight	0 Lm 30° LIGHTING FIXTURE ELECTRICAL DATA Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consult Ø5.51 in Ø140 mm 325° 355° 0.76 lb 343 gr 0.93 lb 423 gr

IO is a LED spotlight miniaturised in a fixture that is so small that it fits on the palm of your hand. Designed for accent lighting applications, its small dimensions mean it can be fitted in display cabinets, shop windows and small places without generating an invasive presence on the scene.

JOKERLIGHT LLC 2750 NW 84th Ave · Doral · FL 33122 (USA) Info@jokerlight.com · www.jokerlight.com

PREMIO ADCV 2017 ORO iF

03-04-25 / 07:00







PRODUCT

Model
Reference
Category


PRODUCT
Beam Mixer Diffuser
0805-01-00
Accessories
NOT SOLD SEPARATELY AFFECTS THE LIGHTING PARAMETERS

The Beam Mixer Diffuser is used to smooth beam artifacts caused by parabolic, Fresnel, or TIR lens collimators without significant broadening.

The unique mixing design provides superior far-field smoothing and color mixing with high on-axis brightness. Compared with traditional diffusers, it maintains higher central beam candlepower (CBCP), and produce less undesirable "field light" at higher angles.







PRODUCT

Model
Reference
Colour
Category

PRODUCT	
Anti-glare Honeycomb Louver	
0806-00-00 WT NT	
WT □ Textured white NT ■ Textured black	
Accessories	
NOT SOLD SEPARATELY	A
AFFECTS THE LIGHTING PARAMETERS	\odot

Accessory made up of louver in the shape of a honeycomb panel to reduce glare and the effects of direct rays of vision.

