io surface



		PRODUCT IO SURFACE UL 30º 2700K WT
	Name Reference	U2630120WT
	Color	Textured white
	Category	SURFACE
Samo		
		LIGHT SOURCE
	Туре	LED
Community of	Gross luminous flux	Depending on Mounting Accessories Lm
	Color temperature	2700 K
	Chromatic stability	MacAdam Step 2
	Color Rendering Index	CRI>90
	Power	Depending on Mounting Accessories W
DIMENSIONS	Current	Depending on Mounting Accessories mA
DIFILMOIONO	LED lifespan	L90B10>55.000h
		LIGHTING FIXTURE PHOTOMETRIC DATA
2.75in [70mm]	Lighting efficiency	89%
	Delivered luminous flux	0 Lm
	Light beam angle	30°
Ø1.42in Ø1.57in		
(36mm) (40mm)		LIGHTING FIXTURE ELECTRICAL DATA
	Driver	LIGHTING FIXTURE ELECTRICAL DATA
(36mm) (40mm)	Driver Power values of the system	
(36mm) (40mm)		Requires remote driver
(36mm) 3.30in (84mm)	Power values of the system	Requires remote driver W
(36mm) (40mm)	Power values of the system Frequency	Requires remote driver W Depending on Mounting Accessories
(36mm) 3.30in (84mm)	Power values of the system Frequency	Requires remote driver W Depending on Mounting Accessories
(36mm) 3.30in (84mm)	Power values of the system Frequency	Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories
(36mm) 3.30in (84mm) ACCESORIES IXER DIFFUSER ANTI-GLARE HONEYCOMB	Power values of the system Frequency Dimming	Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA
(36mm) (40mm) 3.30in (84mm) ACCESORIES	Power values of the system Frequency Dimming Environmental location	Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP
(36mm) 3.30in (84mm) ACCESORIES IXER DIFFUSER ANTI-GLARE HONEYCOMB	Power values of the system Frequency Dimming Environmental location Junction box cover	Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box
(36mm) 3.30in (84mm) ACCESORIES IXER DIFFUSER ANTI-GLARE HONEYCOMB	Power values of the system Frequency Dimming Environmental location Junction box cover Junction box cover color	Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consult
(36mm) 3.30in (84mm) ACCESORIES IXER DIFFUSER ANTI-GLARE HONEYCOMB	Power values of the system Frequency Dimming Environmental location Junction box cover Junction box cover color Junction box cover measurements	Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consult Ø5.51 in Ø140 mm
(36mm) 3.30in (84mm) ACCESORIES XER DIFFUSER ANTI-GLARE HONEYCOMB	Power values of the system Frequency Dimming Environmental location Junction box cover Junction box cover color Junction box cover measurements Swivel angle	Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consult Ø5.51 in Ø140 mm 325°
(36mm) (40mm) 3.30in (84mm) ACCESORIES MIXER DIFFUSER ANTI-GLARE HONEYCOMB	Power values of the system Frequency Dimming Environmental location Junction box cover Junction box cover color Junction box cover measurements Swivel angle Rotation angle	Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consult Ø5.51 in Ø140 mm 325° 355°
(36mm) (40mm) 3.30in (84mm) ACCESORIES	Power values of the system Frequency Dimming Environmental location Junction box cover Junction box cover color Junction box cover measurements Swivel angle Rotation angle Weight	Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consult Ø5.51 in Ø140 mm 325° 355° 0.76 lb 343 gr
(36mm) 3.30in (84mm) ACCESORIES MIXER DIFFUSER ANTI-GLARE HONEYCOMB	Power values of the system Frequency Dimming Environmental location Junction box cover Junction box cover color Junction box cover measurements Swivel angle Rotation angle Weight Packaged weight	Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consult Ø5.51 in Ø140 mm 325° 355° 0.76 lb 343 gr 0.93 lb 423 gr

IO is a LED spotlight miniaturised in a fixture that is so small that it fits on the palm of your hand. Designed for accent lighting applications, its small dimensions mean it can be fitted in display cabinets, shop windows and small places without generating an invasive presence on the scene.

JOKERLIGHT LLC 2750 NW 84th Ave · Doral · FL 33122 (USA) Info@jokerlight.com · www.jokerlight.com

PREMIO ADCV 2017 ORO MF







PRODUCT

Model
Reference
Category


PRODUCT
Beam Mixer Diffuser
0805-01-00
Accessories
NOT SOLD SEPARATELY AFFECTS THE LIGHTING PARAMETERS

The Beam Mixer Diffuser is used to smooth beam artifacts caused by parabolic, Fresnel, or TIR lens collimators without significant broadening.

The unique mixing design provides superior far-field smoothing and color mixing with high on-axis brightness. Compared with traditional diffusers, it maintains higher central beam candlepower (CBCP), and produce less undesirable "field light" at higher angles.







PRODUCT

Model
Reference
Colour
Category

PRODUCT	
Anti-glare Honeycomb Louver	
0806-00-00 WT NT	
WT □ Textured white NT ■ Textured black	
Accessories	
NOT SOLD SEPARATELY	A
AFFECTS THE LIGHTING PARAMETERS	\odot

Accessory made up of louver in the shape of a honeycomb panel to reduce glare and the effects of direct rays of vision.

