iO SURFACE



| | Name | IO SURFACE UL 30º 4000K WT |
|---|--|--|
| | Reference Color | U2630122WT |
| | | |
| | Category | SURFACE |
| STRAND A | | |
| | | LIGHT SOURCE |
| | Туре | LED |
| | Gross luminous flux | Depending on Mounting Accessories Lm |
| | Color temperature | 4000 K |
| | Chromatic stability | MacAdam Step 2 |
| | Color Rendering Index | CRI>90 |
| | Power | Depending on Mounting Accessories W |
| DIMENSIONS | Current | Depending on Mounting Accessories mA |
| DIMENSIONS | LED lifespan | L90B10>55.000h |
| 5.75in (70mm] | Lighting efficiency | 89% |
| Ē | Lighting efficiency | 89% |
| | Delivered luminous flux | 0 Lm |
| | Light beam angle | 30° |
| Q1 (0) Q1 F7 | | |
| Ø1.42in Ø1.57in | | |
| (36mm) (40mm) | | LIGHTING FIXTURE ELECTRICAL DATA |
| | Driver | |
| (36mm) (40mm) • | Driver Power values of the system | LIGHTING FIXTURE ELECTRICAL DATA Requires remote driver W |
| (36mm) (40mm) | | Requires remote driver |
| (36mm) (30in (84mm) | Power values of the system | Requires remote driver W |
| (36mm) (40mm) • | Power values of the system Frequency | Requires remote driver W Depending on Mounting Accessories |
| (36mm) 3.30in (84mm) | Power values of the system Frequency | Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories |
| (36mm) 3.30in (84mm) | Power values of the system Frequency Dimming | Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA |
| (36mm) (40mm) 3.30in (84mm) ACCESORIES MIXER DIFFUSER ANTI-GLARE HONEYCOMB | Power values of the system Frequency Dimming Environmental location | Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP |
| (36mm) 3.30in (84mm) ACCESORIES | Power values of the system Frequency Dimming Environmental location Junction box cover | Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box |
| (36mm) (40mm) 3.30in (84mm) ACCESORIES MIXER DIFFUSER ANTI-GLARE HONEYCOMB | Power values of the system Frequency Dimming Environmental location | Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consult |
| (36mm) 3.30in (84mm) ACCESORIES ACCESORIES ANTI-GLARE HONEYCOMB | Power values of the system Frequency Dimming Environmental location Junction box cover Junction box cover color Junction box cover measurements | Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consult Ø5.51 in Ø140 mm |
| (36mm) (40mm) 3.30in (84mm) ACCESORIES MIXER DIFFUSER ANTI-GLARE HONEYCOMB | Power values of the system Frequency Dimming Environmental location Junction box cover Junction box cover color Junction box cover measurements Swivel angle | Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consult |
| (36mm) 3.30in (84mm) ACCESORIES MMIXER DIFFUSER ANTI-GLARE HONEYCOMB | Power values of the system Frequency Dimming Environmental location Junction box cover Junction box cover color Junction box cover measurements | Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consult Ø5.51 in Ø140 mm 325° 355° |
| (36mm) (40mm) 3.30in (84mm) ACCESORIES MIXER DIFFUSER ANTI-GLARE HONEYCOMB | Power values of the system Frequency Dimming Environmental location Junction box cover Junction box cover color Junction box cover reasurements Swivel angle Rotation angle Weight | Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consult Ø5.51 in Ø140 mm 325° 355° 0.76 lb 343 gr |
| (36mm) (40mm) 3.30in (84mm) ACCESORIES MIXER DIFFUSER ANTI-GLARE HONEYCOMB | Power values of the system Frequency Dimming Environmental location Junction box cover Junction box cover color Junction box cover measurements Swivel angle Rotation angle Weight Packaged weight | Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consult Ø5.51 in Ø140 mm 325° 355° 0.76 lb 343 gr 0.93 lb 423 gr |
| (36mm) 3.30in (84mm) ACCESORIES ACCESORIES ANTI-GLARE HONEYCOMB | Power values of the system Frequency Dimming Environmental location Junction box cover Junction box cover color Junction box cover reasurements Swivel angle Rotation angle Weight | Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories OTHER DATA DAMP Included. For octogonal Junction box Textured white. Other finishing, please consult Ø5.51 in Ø140 mm 325° 355° 0.76 lb 343 gr |

IO is a LED spotlight miniaturised in a fixture that is so small that it fits on the palm of your hand. Designed for accent lighting applications, its small dimensions mean it can be fitted in display cabinets, shop windows and small places without generating an invasive presence on the scene.

JOKERLIGHT LLC 2750 NW 84th Ave · Doral · FL 33122 (USA) Info@jokerlight.com · www.jokerlight.com

PREMIO ADCV 2017 ORO ΠĦ







PRODUCT

| Model |
|-----------|
| Reference |
| Category |


| PRODUCT |
|--|
| Beam Mixer Diffuser |
| 0805-01-00 |
| Accessories |
| NOT SOLD SEPARATELY AFFECTS THE LIGHTING PARAMETERS |

The Beam Mixer Diffuser is used to smooth beam artifacts caused by parabolic, Fresnel, or TIR lens collimators without significant broadening.

The unique mixing design provides superior far-field smoothing and color mixing with high on-axis brightness. Compared with traditional diffusers, it maintains higher central beam candlepower (CBCP), and produce less undesirable "field light" at higher angles.







PRODUCT

| Model |
|-----------|
| Reference |
| Colour |
| Category |

| PRODUCT | |
|---|----------|
| Anti-glare Honeycomb Louver | |
| 0806-00-00 WT NT | |
| WT □ Textured white NT ■ Textured black | |
| Accessories | |
| NOT SOLD SEPARATELY | A |
| AFFECTS THE LIGHTING PARAMETERS | ٢ |

Accessory made up of louver in the shape of a honeycomb panel to reduce glare and the effects of direct rays of vision.

