




DIMENSIONS



| | |
|------------------|---|
| Name | BLACK FOSTER SUSP 1200 UL SPOT 3000K WT |
| Reference | U3211111WT |
| Color | Textured white |
| Category | SUSPENSION |

| | |
|------------------------------|-----------------|
| Type | LED |
| Gross luminous flux | 2100 Lm |
| Color temperature | 3000 K |
| Chromatic stability | MacAdam Step 3 |
| Color Rendering Index | CRI>90 |
| Power | 21 W |
| Current | 700 mA |
| LED lifespan | L80B10 >60.000h |

| | |
|--------------------------------|---------|
| Lighting efficiency | 90% |
| Delivered luminous flux | 1890 Lm |
| Light beam angle | 19° |

| | |
|-----------------------------------|--|
| Driver | Included: ERP-PSB series or similar |
| Power values of the system | 24,00 W |
| Frequency | 50/60 Hz |
| Dimming | 0-10V / TRIAC/ELV dimming only at 120V |

| | |
|----------------------------------|---|
| Environmental location | DAMP |
| Cord Length | MAX. 3.05 m |
| Fast adjustment tensioner | Yes |
| Weight | 7.18 lb 3255 gr |
| Packaged weight | 9.85 lb 4470 gr |
| Packaging dimensions | Ø6.10x50.00 in Ø155x1270 mm |
| Materials | Aluminium - Acrylonitrile Butadiene Styrene - Polycarbonate |

PRODUCT

LIGHT SOURCE

LIGHTING FIXTURE | PHOTOMETRIC DATA

LIGHTING FIXTURE | ELECTRICAL DATA

OTHER DATA



AWARDS




Black Foster Suspension is the product that transfers the claimed effect "The Invisible Black" to a linear suspended system. It is composed by a series of modules which combine light emissions with dark segments. Nevertheless, wether if it is On or Off, Black Foster always preserves the aesthetic of a perfect dark line.

POLAR DIAGRAM



CONICAL DIAGRAM



UGR

| Glare Evaluation According to UGR | | | | | | | | | | | |
|--|-------------|--|------|------|------|-------------|---|------|------|------|------|
| ρ Ceiling | 70 | 70 | 50 | 50 | 30 | 70 | 70 | 50 | 50 | 30 | 30 |
| ρ Walls | 50 | 30 | 50 | 30 | 30 | 50 | 30 | 50 | 30 | 30 | 30 |
| ρ Floor | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 | 20 |
| Room Size X Y | | Viewing direction at right angles to lamp axis | | | | | Viewing direction parallel to lamp axis | | | | |
| 2H | 2H | -1.1 | -0.4 | -0.8 | -0.2 | -0.0 | -0.2 | 0.4 | 0.0 | 0.6 | 0.8 |
| | 3H | 2.4 | 3.0 | 2.7 | 3.3 | 3.5 | 3.7 | 4.3 | 4.0 | 4.5 | 4.8 |
| | 4H | 4.4 | 5.0 | 4.7 | 5.2 | 5.5 | 5.5 | 6.1 | 5.8 | 6.4 | 6.6 |
| | 6H | 6.6 | 7.2 | 7.0 | 7.4 | 7.7 | 7.8 | 8.3 | 8.1 | 8.6 | 8.9 |
| | 8H | 7.8 | 8.3 | 8.1 | 8.6 | 8.9 | 9.0 | 9.5 | 9.4 | 9.8 | 10.1 |
| 4H | 2H | 0.3 | 0.9 | 0.6 | 1.1 | 1.4 | 0.9 | 1.4 | 1.2 | 1.7 | 1.9 |
| | 3H | 4.0 | 4.5 | 4.4 | 4.8 | 5.1 | 4.9 | 5.4 | 5.2 | 5.7 | 6.0 |
| | 4H | 6.1 | 6.5 | 6.5 | 6.9 | 7.2 | 6.9 | 7.3 | 7.3 | 7.7 | 8.0 |
| | 6H | 8.4 | 8.8 | 8.8 | 9.1 | 9.5 | 9.3 | 9.7 | 9.7 | 10.1 | 10.4 |
| | 8H | 9.6 | 9.9 | 10.0 | 10.3 | 10.7 | 10.7 | 11.0 | 11.1 | 11.4 | 11.8 |
| 8H | 2H | 11.1 | 11.4 | 11.5 | 11.8 | 12.2 | 12.2 | 12.5 | 12.7 | 12.9 | 13.3 |
| | 4H | 7.1 | 7.4 | 7.5 | 7.8 | 8.2 | 7.7 | 8.0 | 8.1 | 8.4 | 8.8 |
| | 6H | 9.5 | 9.8 | 10.0 | 10.2 | 10.6 | 10.3 | 10.5 | 10.8 | 11.0 | 11.4 |
| | 8H | 11.0 | 11.1 | 11.4 | 11.6 | 12.1 | 11.8 | 12.0 | 12.3 | 12.5 | 12.9 |
| | 12H | 12.6 | 12.8 | 13.1 | 13.2 | 13.7 | 13.6 | 13.7 | 14.1 | 14.2 | 14.7 |
| 12H | 4H | 7.3 | 7.6 | 7.8 | 8.0 | 8.4 | 7.9 | 8.1 | 8.3 | 8.5 | 9.0 |
| | 6H | 9.9 | 10.1 | 10.4 | 10.5 | 11.0 | 10.6 | 10.8 | 11.0 | 11.2 | 11.7 |
| | 8H | 11.4 | 11.6 | 11.9 | 12.1 | 12.6 | 12.2 | 12.4 | 12.7 | 12.9 | 13.3 |
| Variation of the observer position for the luminaire distances S | | | | | | | | | | | |
| S = 1.0H | +0.2 / -0.1 | | | | | +0.2 / -0.1 | | | | | |
| S = 1.5H | +0.3 / -0.3 | | | | | +0.3 / -0.3 | | | | | |
| S = 2.0H | +0.5 / -0.5 | | | | | +0.5 / -0.5 | | | | | |
| Standard table Correction Summand | --- | | | | | --- | | | | | |
| Corrected Glare Indices referring to 2100lm Total Luminous Flux | | | | | | | | | | | |