



DIMENSIONS

_			
Ø1.65in (42mm)		2.75in (70mm)	
	Ø1.42in (36mm)	2	Ø1.57in (40mm)
			•
			3.30in (84mm)

ACCESORIES





BEAM MIXER DIFFUSER

ANTI-GLARE HONEYCOMB LOUVER

AWARDS









PRODUCT

Name Reference

Color

Category

IO SURFACE UL 20° 2700K NT

U2630110NT

Textured black

SURFACE

	LIGHT SOURCE
Туре	LED
Gross luminous flux	Depending on Mounting Accessories Lm
Color temperature	2700 K
Chromatic stability	MacAdam Step 2
Color Rendering Index	CRI>90
Power	Depending on Mounting Accessories W
Current	Depending on Mounting Accessories mA
LED lifespan	L90B10>55.000h

LIGHTING FIXTURE | PHOTOMETRIC DATA

Lighting efficiency	92%
Delivered luminous flux	0 Lm
Light beam angle	20°

LIGHTING FIXTURE | ELECTRICAL DATA

Driver	Requires remote driver
Power values of the system	W
Frequency	Depending on Mounting Accessories
Dimming	Depending on Mounting Accessories

OTHER DATA

	UTHER DATA
Environmental location	DAMP
Junction box cover	Included. For octogonal Junction box
Junction box cover color	Textured white. Other finishing, please consult
Junction box cover measurements	Ø5.51 in Ø140 mm
Swivel angle	325°
Rotation angle	355°
Weight	0.76 lb 343 gr
Packaged weight	0.93 lb 423 gr
Packaging dimensions	7.99x6.77x2.83 in 203x172x72 mm
Materials	Aluminium - Polycarbonate



IO is a LED spotlight miniaturised in a fixture that is so small that it fits on the palm of your hand. Designed for accent lighting applications, its small dimensions mean it can be fitted in display cabinets, shop windows and small places without generating an invasive presence on the scene.







	PRODUCT
Model	Beam Mixer Diffuser
Reference	0805-01-00
Category	Accessories
	NOT SOLD SEPARATELY


AFFECTS THE LIGHTING PARAMETERS

The Beam Mixer Diffuser is used to smooth beam artifacts caused by parabolic, Fresnel, or TIR lens collimators without significant broadening.

The unique mixing design provides superior far-field smoothing and color mixing with high on-axis brightness. Compared with traditional diffusers, it maintains higher central beam candlepower (CBCP), and produce less undesirable "field light" at higher angles.







PRODUCT

Model	
Reference	
Colour	
Category	

Anti-glare Honeycomb Louver	
0806-00-00 WT NT	
WT ☐ Textured white NT ■ Textured black	
Accessories	
NOT SOLD SEPARATELY	
AFFECTS THE LIGHTING PARAMETERS	

Accessory made up of louver in the shape of a honeycomb panel to reduce glare and the effects of direct rays of vision.

