




DIMENSIONS




ACCESORIES



BEAM MIXER DIFFUSER



ANTI-GLARE HONEYCOMB LOUVER



MINIMAL TRACK OPTIONS

AWARDS



reddot winner 2020  
innovative product



reddot winner 2020  
lighting design



Bronze Delta  
ADI Awards 2020



HONORABLE MENTION  
EUROPEAN  
PRODUCT  
DESIGN  
AWARD



WINNER  
2020



archiproducts  
DESIGN AWARDS  
WINNER 2020

PRODUCT

|           |                              |
|-----------|------------------------------|
| Name      | IO MICRO 24V UL 20° 2700K WT |
| Reference | U3870010WT                   |
| Color     | Textured white               |
| Category  | TRACKLIGHTS                  |

LIGHT SOURCE

|                       |                 |
|-----------------------|-----------------|
| Type                  | LED             |
| Gross luminous flux   | 500 Lm          |
| Color temperature     | 2700 K          |
| Chromatic stability   | MacAdam Step 3  |
| Color Rendering Index | CRI>90          |
| Power                 | 4.7 W           |
| Current               | 400 mA          |
| Efficacy              | 106 Lm/W        |
| LED lifespan          | L80B10 >60.000h |

LIGHTING FIXTURE | PHOTOMETRIC DATA

|                         |        |
|-------------------------|--------|
| Lighting efficiency     | 88%    |
| Delivered luminous flux | 440 Lm |
| Light beam angle        | 20°    |

LIGHTING FIXTURE | ELECTRICAL DATA

|                            |             |
|----------------------------|-------------|
| Driver                     | Included    |
| Power values of the system | 5,00 W      |
| Dimming                    | Dim options |

OTHER DATA


|                        |                                 |
|------------------------|---------------------------------|
| Environmental location | DRY                             |
| Track type             | Minimal Track                   |
| Weight                 | 0.13 lb   60 gr                 |
| Packaged weight        | 0.22 lb   100 gr                |
| Packaging dimensions   | 4.45x3.03x1.5 in   113x77x38 mm |
| Materials              | Aluminium / Polycarbonate       |




\*\*US product only. Not available in Canada. iO Micro 24V is a LED spotlight miniaturised in a fixture that is so small that it fits on the palm of your hand. Designed for accent lighting applications, its small dimensions mean it can be fitted in display cabinets, shop windows and small places without generating an invasive presence on the scene. Created to be placed on a track, it offers all the features of concentrated LED spotlights with a minimalist and hyper-reduced design.



POLAR DIAGRAM



CONICAL DIAGRAM






|           | PRODUCT             |
|-----------|---------------------|
| Model     | Beam Mixer Diffuser |
| Reference | A387-00-00          |
| Category  | Accessories         |

NOT SOLD SEPARATELY  
AFFECTS THE LIGHTING PARAMETERS

The Beam Mixer Diffuser is used to smooth beam artifacts caused by parabolic, Fresnel, or TIR lens collimators without significant broadening.

The unique mixing design provides superior far-field smoothing and color mixing with high on-axis brightness. Compared with traditional diffusers, it maintains higher central beam candlepower (CBCP), and produce less undesirable "field light" at higher angles.






|           | PRODUCT  |
|-----------|--|
| Model     | Anti-glare Honeycomb Louver  |
| Reference | A387-00-01   WT   NT   |
| Category  | Accessories  |
|           | NOT SOLD SEPARATELY<br>AFFECTS THE LIGHTING PARAMETERS  |

Accessory made up of louver in the shape of a honeycomb panel to reduce glare and the effects of direct rays of vision.

24V SYSTEM

# MINIMAL TRACK



**MINIMAL TRACK 24V Profile 2m UL** U384-02-00- | N |

2m = 78.74in

**MINIMAL TRACK 24V Rubber Cable n x 1m UL** U384-00-01- | N |


n = Total Length of System  
1m = 39.37in

24V | Max. 4A

**MINIMAL TRACK 24V Corner 90° 1 Plane UL**

U384-00-02- | N |


Cable Length = 1.38in (35mm)



**MINIMAL TRACK 24V Corner 90° 1 Plane Rounded UL**


U384-00-03- | N |

Cable Length = 1.38in (35mm)



**MINIMAL TRACK 24V Corner 90° 2 Planes UL**

Cable Length = 3.94in (100mm)






**MINIMAL TRACK 24V End Cap UL**

U384-00-05- | N |



**MINIMAL TRACK 24V Connection Box UL**

U384-00-06- | N |



COLOUR | N ■ |




DIM OPTIONS PLEASE CONSULT

INSTALLATION GUIDE  
<https://youtu.be/AqTlsTcSoGA>



24V SYSTEM

# MINIMAL TRACK SUSPENSION



**MINIMAL TRACK 24V Suspension UL**

**Profile 2m**

U384-02-00- | N |

**Profile 2m Initial feed kit UL**

U400-02-10- | N |

**Profile 2m Middle feed kit UL\***


U400-02-20- | N |

\* Unidirectional Middle Feed  
2m = 78.74in

**MINIMAL TRACK 24V Suspension Corner 90° UL**

U400-00-03- | N |

Cable Length = 3.35in (85mm)



**MINIMAL TRACK 24V Suspension UL**

**Rubber Cable n x 1m UL**

U400-00-01- | N |

n = Total Length of System  
1m = 39.37in

24V | Max. 4A

**MINIMAL TRACK 24V Suspension Straight Joiner UL**

U400-00-02- | N |




**MINIMAL TRACK 24V Suspension Kit UL**

U400-02-04- | N |

**MINIMAL TRACK 24V Suspension End Caps UL**

U400-00-05- | N |

Two End Caps Included



COLOUR | N ■ |


DIM OPTIONS PLEASE CONSULT

24V SYSTEM

MINIMAL TRACK SURFACE & SUSPENSION


|   | P                 | V    | D (A x B x C) |   |
|---|-------------------|------|---------------|---|
| <b>MINIMAL TRACK 24V Remote Power Supply UL</b> | <b>U384-00-07</b> | 100W | 24V           | 8.16 x 2.97 x 1.30 in<br>207.2 x 75.4 x 33 mm |

120 & 277 V | 50/60 Hz | NO DIM




|  | P                 | V    | D (A x B x C) |  |
|--|-------------------|------|---------------|--|
| <b>MINIMAL TRACK 24V Dimmable Power Supply UL*</b> | <b>U010-00-01</b> | 60W  | 24V           | 5.83 x 1.68 x 1 in<br>148.2 x 42.6 x 25.4 mm |
|  | <b>U010-00-02</b> | 100W | 24V           | 9.5 x 1.57 x 1 in<br>241.3 x 39.9 x 25.4 mm  |

120 & 277 V | 50/60 Hz | 0-10 V



|  | P                 | V    | D (A x B x C) |  |
|--|-------------------|------|---------------|--|
| <b>MINIMAL TRACK 24V Constant Voltage Dimmer</b> | <b>U010-00-00</b> | 144W | 24V           | 2.86 x 1.18 x 0.71 in<br>72.6 x 30 x 18 mm |

24 V | CASAMBI



UL DROP VOLTAGE TABLE

| POWER | CABLE SECTION | CABLE LENGTH      |                    |                    |                    |
|-------|---------------|-------------------|--------------------|--------------------|--------------------|
|       |               | <16.40 ft<br><5 m | <32.80 ft<br><10 m | <65.62 ft<br><20 m | <98.43 ft<br><30 m |
| 60 W  | AWG18         | 98.43 ft<br>30 m  | 98.43 ft<br>30 m   | 65.62 ft<br>20 m   | 32.80 ft<br>10 m   |
|       | AWG16         | 98.43 ft<br>30 m  | 98.43 ft<br>30 m   | 98.43 ft<br>30 m   | 65.62 ft<br>20 m   |
| 96 W  | AWG18         | 65.62 ft<br>20 m  | 32.80 ft<br>10 m   | X                  | X                  |
|       | AWG16         | 65.62 ft<br>20 m  | 65.62 ft<br>20 m   | 32.80 ft<br>10 m   | X                  |

PHASE CUT AND DMX DIM OPTIONS PLEASE CONSLT | \*POWER SUPPLY REQUIRES AN ENCLOSURE FOR INSTALLATION. ENCLOSURE NOT PROVIDED