BLACK FOSTER

٥) (

0

DIMENSIONS

3.82in (97mm)

1.73in (44mm)

 \odot

۲

0

16.97in (431mm)

57in (40m



Reference	4
Color	
Category	
Туре	
Gross luminous flux	
Color temperature	
Chromatic stability	
Color Rendering Index	
Power	
Current	
LED lifespan	
Lighting efficiency	
Delivered luminous flux	
Delivered luminous flux Light beam angle	
Light beam angle Driver	
Light beam angle	
Light beam angle Driver	
Light beam angle Driver Power values of the system	
Light beam angle Driver Power values of the system Frequency	
Light beam angle Driver Power values of the system Frequency	
Light beam angle Driver Power values of the system Frequency	
Light beam angle Driver Power values of the system Frequency Dimming	
Light beam angle Driver Power values of the system Frequency Dimming IC Rated	
Light beam angle Driver Power values of the system Frequency Dimming IC Rated Environmental location	
Light beam angle Driver Power values of the system Frequency Dimming IC Rated Environmental location Recess measurements	
Light beam angle Driver Power values of the system Frequency Dimming IC Rated Environmental location Recess measurements Weight	

PRODUCT
BLACK FOSTER TRI 10 UL FLOOD 2700K N
U3185010N
Matt black
CEILING RECESSED

LIGHT SOURCE

LED	
Depending on Mounting Accessories Lm	
2700 K	
MacAdam Step 3	
CRI>90	
Depending on Mounting Accessories W	
Depending on Mounting Accessories mA	
L90B10>102.000h	

LIGHTING FIXTURE | PHOTOMETRIC DATA

92%	
0 Lm	
38°	

LIGHTING FIXTURE | ELECTRICAL DATA

Requires remote driver	
W	
Depending on Mounting Accessories	
Depending on Mounting Accessories	

OTHER DATA

25	
AMP	
97 x 17.20 50 x 437	
51 lb 684 gr	
22 lb 1009 gr	
4.13x22.83 in Ø105x580 mm	
uminium - Acrylonitrile Butadiene Styrene - Polycarbo	onate







Black Foster is our lineal recessed luminaire with "The invisible black" effect, also available in a trimless version. Hiding the source of light, Black Foster stands out for its visual comfort and its elegance.

