



### DIMENSIONS



### ACCESSORIES



TRACK 48V OPTIONS

### AWARDS



### PRODUCT

Name SIX XS 48V UL DIM DALI 34° 2700K WT

Reference U3350230WT

Color Textured white

Category TRACKLIGHTS

### LIGHT SOURCE

Type LED

Gross luminous flux 470 Lm

Color temperature 2700 K

Chromatic stability MacAdam Step 2

Color Rendering Index CRI>90

Power 4.5 W

Current 500 mA

Efficacy 104 Lm/W

LED lifespan L90B10>55.000h

### LIGHTING FIXTURE | PHOTOMETRIC DATA

Lighting efficiency 88%

Delivered luminous flux 414 Lm

Light beam angle 34°

### LIGHTING FIXTURE | ELECTRICAL DATA

Driver Included

Power values of the system 5,00 W

Dimming DALI

### OTHER DATA

DAMP

Swivel angle 310°

Rotation angle 360°

Track type Track 48V

Weight 0.25 lb | 112 gr

Packaged weight 0.35 lb | 160 gr

Packaging dimensions 7.48x5.71x0.94 in | 190x145x24 mm

Materials Aluminium - Polycarbonate



Environmental location

Swivel angle

Rotation angle

Track type

Weight

Packaged weight

Packaging dimensions


Materials

SIX 48V is a family of spotlights for track applications that stands out for its minimalistic presence and maximum light output. Available in four different sizes, its body encloses an innovative combination of reflector and lens which allows SIX to direct light with the maximum uniformity in a very small distance. SIX can be freely orientated in any direction.

POLAR DIAGRAM



CONICAL DIAGRAM





TRACK 48V TRIMLESS UL

TRACK 48V TRIMLESS 3.28ft (1m) UL	U338-01-00-	N	WT
TRACK 48V TRIMLESS 6.56ft (2m) UL	U338-02-00-	N	WT
TRACK 48V TRIMLESS Corner 90° One Plane UL	U338-06-00-	N	WT
TRACK 48V TRIMLESS Corner 90° Two Planes UL	U338-07-00-	N	WT

PLASTERBOARD CEILING MANDATORY THICKNESS 0.50in (12.5mm)  
RECOMMENDED FOR INSTALLATIONS WHERE THE PROFILE CAN BE INSTALLED BEFORE THE FALSE PLASTERBOARD CEILING

TRACK 48V TRIMLESS  
Corner 90° One Plane UL



\*Electrical connection not included

TRACK 48V TRIMLESS  
Corner 90° Two Planes UL



\*Electrical connection not included

TRIMLESS INSTALLATION GUIDE  
<https://youtu.be/SVWNEfblfVY>



TRACK 48V SURFACE UL

TRACK 48V SURFACE 3.28ft (1m) UL	U338-11-00-	NT	WT
TRACK 48V SURFACE 6.56ft (2m) UL	U338-12-00-	NT	WT
TRACK 48V SURFACE Corner 90° One Plane UL	U338-14-00-	NT	WT

TRACK 48V SURFACE  
Corner 90° One Plane UL




\*Electrical connection not included




TRACK 48V SURFACE SHORT UL

TRACK 48V SURFACE SHORT 3.28ft (1m) UL	U338-21-00-	NT	WT
TRACK 48V SURFACE SHORT 6.56ft (2m) UL	U338-22-00-	NT	WT
TRACK 48V SURFACE SHORT Corner 90° One Plane UL	U338-24-00-	NT	WT

TRACK 48V SURFACE SHORT  
Corner 90° One Plane UL



\*Electrical connection not included



		P	V	D
<b>CONSTANT VOLTAGE LED POWER SUPPLY</b>	<b>U100-00-78</b>	96W	48V	8.16 x 2.97 x 1.30 in 207 x 75.4 x 33 mm

120 & 277 V | 50/60 Hz

UL DROP VOLTAGE TABLE

POWER	CABLE SECTION	CABLE LENGTH			
		16.40ft 5m	32.80ft 10m	65.62ft 20m	98.43ft 30m
96W	AWG 16	164ft	164ft	131.32ft	82ft
		50m	50m	40m	25m

ALL 48V TRACK UL



Live-End Connector 48V UL  
U338-00-01- | N | W |



L-JOINT Connector 48V UL  
U338-00-12- | N | W |



Corner 90° Connector One Plane 48V UL  
U338-00-24- | N | W |

\*Not suitable for trimless version



Central Connector 48V UL  
U338-00-02- | N | W |



Wireless Control 48V UL  
U434-01-31- | N | W |  
Casambi/AAG Stucchi App



Cover Gap 3,28 ft (1m) 48V UL  
U338-00-30- | N |

TRIMLESS 48V UL



Trimless T-Bracket 48V UL  
U338-00-03



Clamp for M6 ROD UL  
U338-00-09  
\*See accessories quantities



Trimless Long T-Bracket 48V UL  
U338-00-04



Track Clamp UL  
U338-00-10  
\*See accessories quantities



Trimless Straight Joiners 48V (2 units) UL  
U338-00-05- | N | WT |



Suspension Kit UL  
U338-00-08  
\*See accessories quantities




Trimless Plaster Installation Guard  
3.28ft (1m) 48V UL  
U338-00-21

\* SUGGESTED MOUNTING ACCESSORIES QUANTITIES

- 3.28ft (1000mm) - 2 Pcs.
- 6.56ft (2000mm) - 3 Pcs.
- 9.84ft (3000mm) - 4 Pcs.

SURFACE, SUSPENSION , SURFACE SHORT & SUSPENSION SHORT 48V UL



Surface Straight Joiner 48V UL  
U338-00-11

TRIMLESS, SURFACE & SUSPENSION 48V UL



End 48V UL

U338-00-06- | NT | WT |



End feed 48V UL

U338-00-07- | NT | WT |

SURFACE SHORT & SUSPENSION SHORT 48V UL



Short End 48V UL

U338-00-18- | NT | WT |



Short End feed 48V UL

U338-00-19- | NT | WT |

SUSPENSION & SUSPENSION SHORT 48V UL



Suspension Kit 48V (2 units) UL

U338-00-15- | NT | WT |



Suspension feed Kit 48V UL

U338-00-17- | N | W |



DIM

\*For remote power supply