



DIMENSIONS

Ø1.65in (42mm)		2.75in (70mm)	
	Ø1.42in (36mm)	(1)	Ø1.57in (40mm)
			3.30in (84mm)

ACCESORIES





BEAM MIXER DIFFUSER

ANTI-GLARE HONEYCOMB

AWARDS









PRODUCT IO SURFAC

Name Reference

Color

Category

IO SURFACE UL 30° 3000K NT U2630121NT

Textured black
SURFACE

Type
Gross luminous flux
Color temperature
Chromatic stability
Color Rendering Index
Power
Current
LED lifespan

LIGHT SOURCE

LED

Depending on Mounting Accessories Lm

3000 K

MacAdam Step 2

CRI>90

Depending on Mounting Accessories W

Depending on Mounting Accessories mA

L90B10>55.000h

Lighting efficiency Delivered luminous flux Light beam angle

89% 0 Lm 30°

LIGHTING FIXTURE | PHOTOMETRIC DATA

LIGHTING FIXTURE | ELECTRICAL DATA

Driver
Power values of the system
Frequency
Dimming

Requires remote driver W Depending on Mounting Accessories Depending on Mounting Accessories

Environmental location Junction box cover Junction box cover color Junction box cover measurements Swivel angle Rotation angle Weight Packaged weight Packaging dimensions Materials

DAMP	
Includ	ed. For octogonal Junction box
Textur	red white. Other finishing, please consult
Ø5.51	in Ø140 mm
325°	
355°	
0.76 lb) 343 gr
0.93 lb	o 423 gr
7.99x6	.77x2.83 in 203x172x72 mm
Alumi	nium - Polycarhonate



OTHER DATA

IO is a LED spotlight miniaturised in a fixture that is so small that it fits on the palm of your hand. Designed for accent lighting applications, its small dimensions mean it can be fitted in display cabinets, shop windows and small places without generating an invasive presence on the scene.







	PRODUCT
Model	Beam Mixer Diffuser
Reference	0805-01-00
Category	Accessories
	NOT SOLD SEPARATELY


AFFECTS THE LIGHTING PARAMETERS

The Beam Mixer Diffuser is used to smooth beam artifacts caused by parabolic, Fresnel, or TIR lens collimators without significant broadening.

The unique mixing design provides superior far-field smoothing and color mixing with high on-axis brightness. Compared with traditional diffusers, it maintains higher central beam candlepower (CBCP), and produce less undesirable "field light" at higher angles.







PRODUCT

Model	
Reference	
Colour	
Category	

Anti-glare Honeycomb Louver			
0806-00-00 WT NT			
WT ☐ Textured white NT ■ Textured black			
Accessories			
NOT SOLD SEPARATELY			
AFFECTS THE LIGHTING PARAMETERS			

Accessory made up of louver in the shape of a honeycomb panel to reduce glare and the effects of direct rays of vision.

