



DIMENSIONS

Ø1.65in (42mm)		2.75in [70mm]
	Ø1.42in (36mm)	Ø1.57in (40mm)
		3.30in (84mm)

ACCESORIES





BEAM MIXER DIFFUSER

ANTI-GLARE HONEYCOMB LOUVER

AWARDS









	PRODUCT
Name	IO SURFACE UL 20° 4000K NT
Reference	U2630112NT
Color	Textured black
Category	SURFACE
	LIGHT SOURCE
Туре	LED
Gross luminous flux	Depending on Mounting Accessories Lm
Color temperature	4000 K
Chromatic stability	MacAdam Step 2
Color Rendering Index	CRI>90
	Depending on Mounting Accessories W
Power	Depending on Mounting Accessories W
Current	Depending on Mounting Accessories w
	-
Current LED lifespan Lighting efficiency	Depending on Mounting Accessories mA L90B10>55.000h LIGHTING FIXTURE PHOTOMETRIC DATA 92%
Current LED lifespan Lighting efficiency Delivered luminous flux	Depending on Mounting Accessories mA L90B10>55.000h LIGHTING FIXTURE PHOTOMETRIC DATA 92% 0 Lm
Current LED lifespan Lighting efficiency	Depending on Mounting Accessories mA L90B10>55.000h LIGHTING FIXTURE PHOTOMETRIC DATA 92%
Current LED lifespan Lighting efficiency Delivered luminous flux	Depending on Mounting Accessories mA L90B10>55.000h LIGHTING FIXTURE PHOTOMETRIC DATA 92% 0 Lm 20°
Current LED lifespan Lighting efficiency Delivered luminous flux Light beam angle	Depending on Mounting Accessories mA L90B10>55.000h LIGHTING FIXTURE PHOTOMETRIC DATA 92% 0 Lm 20° LIGHTING FIXTURE ELECTRICAL DATA
Current LED lifespan Lighting efficiency Delivered luminous flux Light beam angle	Depending on Mounting Accessories mA L90B10>55.000h LIGHTING FIXTURE PHOTOMETRIC DATA 92% 0 Lm 20° LIGHTING FIXTURE ELECTRICAL DATA Requires remote driver

Junction box cover
Junction box cover color
Junction box cover measurements
Swivel angle
Rotation angle
Weight

Environmental location

Included. For octogonal Junction box Textured white. Other finishing, please consult Ø5.51 in | Ø140 mm 325° 355° 0.76 lb | 343 gr Packaged weight 0.93 lb | 423 gr Packaging dimensions 7.99x6.77x2.83 in | 203x172x72 mm Materials Aluminium - Polycarbonate



IO is a LED spotlight miniaturised in a fixture that is so small that it fits on the palm of your hand. Designed for accent lighting applications, its small dimensions mean it can be fitted in display cabinets, shop windows and small places without generating an invasive presence on the scene.







	PRODUCT
Model	Beam Mixer Diffuser
Reference	0805-01-00
Category	Accessories
	NOT SOLD SEPARATELY


AFFECTS THE LIGHTING PARAMETERS

The Beam Mixer Diffuser is used to smooth beam artifacts caused by parabolic, Fresnel, or TIR lens collimators without significant broadening.

The unique mixing design provides superior far-field smoothing and color mixing with high on-axis brightness. Compared with traditional diffusers, it maintains higher central beam candlepower (CBCP), and produce less undesirable "field light" at higher angles.







PRODUCT

Model	
Reference	
Colour	
Category	

Anti-glare Honeycomb Louver	
0806-00-00 WT NT	
WT ☐ Textured white NT ■ Textured black	
Accessories	
NOT SOLD SEPARATELY	
AFFECTS THE LIGHTING PARAMETERS	

Accessory made up of louver in the shape of a honeycomb panel to reduce glare and the effects of direct rays of vision.

