BLACK FOSTER





DIMENSIONS

2.20in (56mm)

0

8.98in [228mm]

1.61in [41mm]

| Nam |
|----------|
| Referenc |
| Colo |
| Categor |
| |

| Туре |
|-----------------------|
| |
| Gross luminous flux |
| Color temperature |
| Chromatic stability |
| Color Rendering Index |
| Power |
| Current |
| LED lifespan |

| | _ |
|------------------------|---|
| Lighting efficience | y |
| Delivered luminous flu | x |
| Light beam ang | e |
| | _ |

| Driver | |
|----------------------------|--|
| Power values of the system | |
| Dimming | |

| Environmental location |
|------------------------|
| Weight |
| Packaged weight |
| Packaging dimensions |
| Materials |

| PRODUCT |
|-------------------------------------|
| BLACK FOSTER ASYMM REC 5 UL 2700K N |
| U3744010N |
| Matt black |
| CEILING RECESSED |

LIGHT SOURCE

| LED |
|--------------------------------------|
| Depending on Mounting Accessories Lm |
| 2700 K |
| MacAdam Step 3 |
| CRI>90 |
| Depending on Mounting Accessories W |
| Depending on Mounting Accessories mA |
| L90B10>102.000h |
| |

LIGHTING FIXTURE | PHOTOMETRIC DATA

| 90% | | |
|------|--|--|
| 0 Lm | | |
| 38° | | |
| | | |

LIGHTING FIXTURE | ELECTRICAL DATA

| Requires remote driver | |
|-----------------------------------|--|
| W | |
| Depending on Mounting Accessories | |

OTHER DATA

| | | | |
|-------------|-------|------|--|
| 0.75 lb 3 | 40 gr | | |
| 0.96 lb 4 | 35 gr | | |

Aluminium / Acrylonitrile Butadiene Styrene





Black Foster is the product that transfers the claimed effect " The Invisible Black" to a recessed-isolated lineal luminary; also available in trimless version. If we take a closer view to the recessed model, its bezel is so thin than when lighted up, it is unperceived; offering an aesthetic of "visual trimless". Black Foster stands out for its refinement, its visual comfort and for almost completely hide the source of light from the human eye range.





POLAR DIAGRAM





